

ignition sources away from the material handling point.
Never use welding or cutting torches on or near container, even when empty.
Residual vapor may ignite explosively.

===== SECTION V - REACTIVITY DATA =====

STABILITY: Stable

CONDITIONS TO AVOID:

INCOMPATIBILITY (MATERIALS TO AVOID): Alkalies.

Oxidizing agents.

Acids.

Amines.

HAZARDOUS DECOMPOSITION PRODUCTS: May produce fumes if heated to decomposition.

Fumes may contain: carbon monoxide and/or carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur.

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Anesthetic. Irritation of the respiratory tract or acute nervous system depression characterized by the following progressive steps: dizziness, staggering, confusion, unconsciousness or coma.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Irritant.

Liquid can be a severe irritant to the eyes.

Repeated skin contact may cause sensitization.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

This product contains one or more materials which can be absorbed, in toxic amounts, through intact skin.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Ingestion of industrial coatings is not considered a likely hazard. In the event of an occurrence, consult a physician.

CHRONIC HEALTH HAZARD INFORMATION:

Ethylene glycol monopropyl ether may cause blood disorders based on animal testing data.

Animal testing indicates that hemolytic effects may occur from overexposure to ethylene glycol monobutyl ether. The liver and kidney may be target organs.

Relevance to humans is uncertain.

See additional precautions detailed in Section IX.

CARCINOGENICITY INFORMATION:

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION: Remove to fresh air. Restore breathing as necessary. **SPLASH (EYES):** Flush immediately with large amounts of water for at least 15 minutes. Take to a physician for medical treatment. **SPLASH (SKIN):** Wash affected areas with soap and water. Remove contaminated clothing. Consult a physician if irritation persists. **INGESTION:** Do not induce vomiting. Consult a physician or poison control center immediately. Treat symptomatically.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Remove all potential sources of ignition (flames, hot surfaces, electrical, static and/or frictional sparks). Avoid breathing of dust or vapors. Ventilate area. Remove with inert absorbent using non-sparking tools. Before beginning clean-up, refer to hazard cautions in other sections of this sheet.

WASTE DISPOSAL METHOD:

Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.

See additional precautions SEC.IX.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Keep closure tight and container upright to prevent leaking. Store containers out of sun and away from heat..See additional precautions SEC.IX.

OTHER PRECAUTIONS:

Do not get in eyes. Avoid skin contact. Prevent prolonged or repeated breathing of vapor or spray mist.

See additional precautions SEC.IX.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION:

Outdoor or open areas - Use approved mechanical filter respirator to remove solid airborne particulates of overspray during spray application. Restricted ventilation areas - Use approved chemical/mechanical filters designed to remove a combination of vapors and particulates. Confined areas - Use approved air line type respirators or hoods.

VENTILATION:

Provide sufficient volume and pattern to maintain TLV-TWA below acceptable limits (see Section II). Eliminate ignition source if flammable mixtures will be encountered.

PROTECTIVE GLOVES:

Recommended, and required for prolonged or repeated contact.

EYE PROTECTION:

Use approved safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Protective cap and coverables are recommended. Remove and wash contaminated clothing before re-use. Wear chemical and solvent resistant shoes.

===== SECTION IX - ADDITIONAL INFORMATION - =====

All containers should be grounded when handling or transferring.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse, by deliberately concentrating and inhaling vapors of this product, may be harmful or fatal.

Contains water! DO NOT FREEZE.

This product is part of a two-component system. Precautions on other component apply to mixture. Consult the second component MSDS before blending.

=====

CINTECH INDUSTRIAL COATINGS believes the information contained herein is accurate. However, the Company assumes no liability for the accuracy or completeness of the information. All materials may present unknown health hazards and should be used with caution. Final determination of suitability of the material is the sole responsibility of the user.