

2217 LANGDON FARM RD. \* CINCINNATI, OHIO 45237-4792  
Ph: (513) 631-4270 \* FAX: (513) 366-4444

# PRODUCT INFORMATION SHEET

CUSTOMER: \_\_\_\_\_ DATE: \_\_\_\_\_  
LOCATION: \_\_\_\_\_ REPRESENTATIVE: \_\_\_\_\_  
PRODUCT NO.: 040072 DESCRIPTION: W/R ENAMEL

## SPECIFICATION

VISCOSITY: 19 - 23 SECS. (#2 ZAHN CUP) LBS/GAL: 8.58  
% SOLIDS (WGT): 21.5 - 22.5 VOC: 3.44 LBS/GAL  
% SOLIDS (VOLUME): 17.0 - 18.0 COLOR(S): STANDARD  
GLOSS: 75+ (60 DEG. METER)  
THEORETICAL COVERAGE: 710 FT<sup>2</sup>/GAL @ 0.4 MIL(S) (NO LOSS)

## APPLICATION

METHOD: SPRAY RECOMMENDED BUILD: 0.4 - 0.5 MIL(S) (DRY).  
APPLICATION VISCOSITY: 19 - 23 SEC. (#2 ZAHN CUP)  
RECOMMENDED REDUCTION: NONE WITH: NONE  
COMPATIBLE FAST SOLVENT: COMPATIBLE SLOW SOLVENT: WATER  
OTHER RECOMMENDATIONS:

## SUBSTRATE

SURFACE TO BE COATED: STEEL RECOAT SCHEDULE:  
APPLY OVER  UNDER CLEAN, PROPERLY PREPARED SURFACE

## DRY SCHEDULE

AIR DRY SET-TO-TOUCH: TACK FREE: HANDLE: PACK PARTS:  
HEAT CURE  FLASH TIME: 5 MINUTES SCHEDULE: 10 MINUTES @ 120 DEG. F

## TYPICAL PERFORMANCE:

PROD. NO. 040072 SHOULD BE USED WITHIN 6 MONTHS FROM DATE OF

### DISCLAIMER

ANY RECOMMENDATIONS WE MAKE WITH RESPECT TO OUR PRODUCTS ARE BASED UPON MANY YEARS OF EXPERIENCE IN THE MANUFACTURE OF INDUSTRIAL PRODUCT FINISHES AND ON TESTS WE DEVELOPED AND BELIEVE TO BE RELIABLE: HOWEVER, WE DO NOT ASSUME ANY RESPONSIBILITY FOR ANY OF THOSE RECOMMENDATIONS OR ANY SUGGESTIONS MADE BY OUR REPRESENTATIVES. THE USE AND APPLICATION OF OUR PRODUCTS IS BEYOND OUR CONTROL AND **WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE**, AND WE DISCLAIM RESPONSIBILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND WE DISCLAIM RESPONSIBILITY FOR THE RESULTS, INCLUDING DAMAGE